

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.


**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<p>(51) International Patent Classification ⁵ : A47L 15/00, 15/02, 15/08 A47L 15/14, 15/22, H02K 15/02 H02P 1/50</p>	<p>A1</p>	<p>(11) International Publication Number: WO 93/12706</p> <p>(43) International Publication Date: 8 July 1993 (08.07.93)</p>
<p>(21) International Application Number: PCT/NZ92/00008</p> <p>(22) International Filing Date: 18 December 1992 (18.12.92)</p> <p>(30) Priority data: 241093 20 December 1991 (20.12.91) NZ</p> <p>(71) Applicant (for all designated States except US): FISHER & PAYKEL LIMITED [NZ/NZ]; 78 Springs Road, East Tamaki, Auckland (NZ).</p> <p>(72) Inventors; and (75) Inventors/Applicants (for US only) : SARGEANT, Adrian, Anthony [NZ/NZ]; 290 Helensburgh Road, Dunedin (NZ). CURRIE, William, Hugh [NZ/NZ]; 120 Arthur Street, Dunedin (NZ). OUWENS, Willem [NZ/NZ]; Old Main Road, Henley R.D. 1, Outram (NZ). BRACE, Philip, John [NZ/NZ]; 112 Shackleton Road, Epsom, Auckland (NZ). TODD, Robert, William [NZ/NZ]; 100 Brockville Road, Glenross, Dunedin (NZ). SCHOLZ, Hans-Joachim [NZ/NZ]; 13 Scroggs Hill Road, Brighton, Otago (NZ).</p>		<p>(74) Agents: MOON, Kenneth, R. et al.; Huddart Parker Building, Post Office Square, Wellington (NZ).</p> <p>(81) Designated States: AT, AU, BB, BG, BR, CA, CH, CS, DE, DK, ES, FI, GB, HU, JP, KP, KR, LK, LU, MG, MN, MW, NL, NO, NZ, PL, PT, RO, RU, SD, SE, UA, US, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, SN, TD, TG).</p> <p>Published With international search report.</p>

(54) Title: DISHWASHER



(57) Abstract

A dishwasher having spray arm, motor and pump components configured and mounted so as to occupy very low height. In one form the complete wash system is arranged as a drawer which slides in and out of a cabinet. The cabinet opening is stiffened against racking forces by incorporating an inverse portal frame in the opening flange. A synchronous AC motor is used with the rotor running within the wash chamber driving a wash pump integrated with a rotating spray arm.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	FR	France	MR	Mauritania
AU	Australia	GA	Gabon	MW	Malawi
BB	Barbados	GB	United Kingdom	NL	Netherlands
BE	Belgium	GN	Guinea	NO	Norway
BF	Burkina Faso	GR	Greece	NZ	New Zealand
BG	Bulgaria	HU	Hungary	PL	Poland
BJ	Benin	IE	Ireland	PT	Portugal
BR	Brazil	IT	Italy	RO	Romania
CA	Canada	JP	Japan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SK	Slovak Republic
CI	Côte d'Ivoire	LJ	Liechtenstein	SN	Senegal
CM	Cameroon	LK	Sri Lanka	SU	Soviet Union
CS	Czechoslovakia	LU	Luxembourg	TD	Chad
CZ	Czech Republic	MC	Monaco	TG	Togo
DE	Germany	MG	Madagascar	UA	Ukraine
DK	Denmark	ML	Mali	US	United States of America
ES	Spain	MN	Mongolia	VN	Viet Nam
FI	Finland				

"DISHWASHER"**FIELD OF THE INVENTION**

5 This invention relates to dishwashers, and in particular, but not solely, domestic dishwashers.

DESCRIPTION OF RELATED ART

10 Conventional domestic front loading dishwashers provide two racks for stacking dishes, one in the lower zone of the wash chamber and the other in the upper zone. Such dishwashers are normally designed to fit under a typical domestic kitchen bench top with a maximum height of 900mm. Generally the lower rack is designed to take larger dishes, e.g. plates up to 280mm in diameter, and because of the overall height limitation the upper rack can only take lower height dishes. Such dishwashers lack flexibility in that they cannot efficiently wash (in a single wash) dish loads made up of a mix of dish sizes
15 other than that dictated by the manufacturer. For example, a load of large diameter plates exceeding the number that can be accommodated in the lower rack must be cleaned using two completely separate wash cycles, even although the top rack could be empty. Further, it is not feasible to load soiled dishes unless all cleaned dishes are first removed. In addition it is not efficient
20 to wash less than full loads. Washing must be deferred until the dishwasher has been completely filled.

The first two problems identified above can be overcome to some extent by the use of two dishwashers. However, cost and space factors usually mean this is not a viable option. The present invention proposes a solution to
25 the above problems by providing a smaller dishwasher intended to be used as one module in a two-module pair. The dishwasher is of very low height to allow the option of "over and under" stacking of two modules below a kitchen bench.

Construction of a low height machine imposes severe design constraints.
30 In most conventional dishwashers components such as the wash pump and drain pump, along with associated electric motors, are mounted under the wash chamber thereby consuming height which could be available to the wash chamber. In US 3,587,939 (Nystuen et al) wash and drain pumps driven

by a common induction motor are disclosed which are located inside the wash chamber and the motor is operable submerged in the wash water. A disadvantage of this system is the need to seal the motor stator from the wash liquid. A drain pump which operates with a submerged motor rotor and a stator external to the pump casing is disclosed in EP 287,984 (Askoll SPA). However this pump requires the use of two separate chambers for the motor rotor and pump impeller respectively and is not easy to service in use. Further, it is not possible to use the motor disclosed to additionally drive a wash pump.

10 EP 76,739 (Esswein), EP 268,835 (Industrie Zanussi) and US 3,810,480 (Smith and Faust) disclose other constructions where the wash and drain pumps are driven by a common motor where the direction of rotation of the motor determines which pump is operable. These constructions do not significantly reduce the height requirements of the wash system.

15 US 3,645,453 (Morgan) and GB 1,119,449 disclose dishwasher spray arms which incorporate as an integral part the casing of the wash pump to produce a low height wash pump located within the wash chamber. However, these systems require a motor external to the wash chamber and the need for a dynamic seal for the motor drive shaft where it passes into the wash chamber.

20 A small top loading dishwasher ("Bauknecht") for mounting within a kitchen cupboard and able to be extended from the cupboard on slides has been manufactured by Philips Appliances, but this does not address the problems outlined above, and in particular requires users to lift the wash chamber lid after cupboard opening and complete withdrawal of the machine from the cupboard.

25 To allow for accurate measuring of wash liquid volume, and pre-heating of water before it is dumped into a hot wash chamber, it is known to use a separate water reservoir tank fed from the household cold water supply. Such systems are disclosed in DE 3,531,095, GB 2,139,083, GB 2,139,084 (Bosch - Siemens). Further the use of such a tank filled with cold water to condense out water vapour in the wash chamber during drying cycles is disclosed in DE, 2,730,489 (Bosch - Siemens). In all of these arrangements fabricated metal

tanks are used which are mounted on a metal wash chamber and this increases manufacturing costs.

Currently available dishwashers use metal sheathed resistance heating elements mounted above the floor of the wash chamber. It is known to fabricate electrical heating elements using thick film resistors deposited on a substrate. Such heaters have been used in very low power applications such as in energy regulators. US 4,843,218 (Bosch - Siemens) proposes the use of thick film technology to fabricate an electric cooking element. Such prior art does not, however, envisage a thick film resistive heater for application in a dishwasher where efficient and direct heating of wash liquid is required.

SUMMARY OF THE INVENTION

It is an object of the present invention to provide a dishwasher which will go some way towards overcoming the abovementioned disadvantages or which will at least provide the public with a useful choice.

In the first aspect the invention consists in a dishwasher comprising:

- a) a wash chamber adapted to accommodate dishes and within which wash liquid is circulated,
- b) a well provided in the floor of said chamber,
- c) an electric motor including:
 - (i) a rotor mounted within said well, and
 - (ii) a co-acting stator mounted outside said wash chamber on the exterior surface of said well, and
- d) a wash pump having an impeller driven by said rotor.

In second aspect the invention consists in a dishwasher comprising:

- a) a wash chamber adapted to accommodate dishes and within which wash liquid is circulated,
- b) a well provided in the floor of said chamber,
- c) an electric motor including:
 - (i) a rotor mounted within said well, and
 - (ii) a co-acting stator mounted outside said wash chamber on the exterior surface of said well,
- d) a wash chamber drain pump including:

- (i) an impeller located in said well together with said motor rotor, said impeller being driven by said rotor,
- (ii) a casing formed by the well walls proximate to said impeller,
- 5 (iii) a liquid inlet and a liquid outlet in said casing, and
- e) a liquid passageway connecting said wash chamber with said casing inlet, said rotor when rotated in a first direction causing said pump to drain wash liquid from the wash chamber for delivery at said liquid outlet.

- 10 In a third aspect the invention consists in a dishwasher comprising:
- a wash chamber adapted to accommodate dishes and within which wash liquid is circulated,
 - an electric motor for driving a centrifugal wash pump having a vertical axis drive shaft projecting centrally into the floor of said wash chamber,
 - 15 a wash pump impeller driven by said motor shaft,
 - a spray arm having liquid discharge nozzles rotatably supported in the bottom of said wash chamber for rotation about said wash pump impeller, said spray arm having central internal upper and side surfaces which define a co-acting casing for said wash pump impeller and which define a volute which
 - 20 allows delivery of wash liquid pumped from said casing to said nozzles, said spray arm central under surface being open to provide an axial flow inlet for said wash pump,
 - a first annular aperture provided in the floor of said wash chamber immediately below and in registration with the wash pump inlet,
 - 25 a second substantially annular aperture provided in the floor of said wash chamber having a diameter much greater than said first aperture, and
 - a plenum below the floor of said wash chamber which allows liquid to flow from the second annular aperture to the first annular aperture for induction up into said wash pump.

- 30 In a fourth aspect the invention consists in a dishwasher comprising:
- a wash chamber adapted to accommodate dishes and within which wash liquid is circulated,
 - an electric motor for driving a wash pump,

a wash pump having an inlet and an outlet impeller driven by said motor,
a spray arm generating means which discharges within said wash chamber and which is supplied with wash liquid from the outlet of said wash pump,

5 a substantially annular aperture provided in the floor of said wash chamber having an outer diameter which is significant compared to the dimensions of the wash chamber floor, and

a plenum below the floor of said wash chamber which allows liquid to flow from said annular aperture to the inlet of said wash pump.

10 In a fifth aspect the invention consists in a dishwasher comprising: a wash chamber adapted to receive dishes to be cleaned, a pump for circulating wash liquid within said chamber, a spray arm having nozzles therein which is rotatably mounted adjacent to the floor of said chamber which receives pressurized wash liquid from said pump and dispenses it through said nozzles
15 into said chamber, and an electrical heating plate which forms part of the wash chamber surface such that at least a portion of the circulating wash liquid comes into thermal contact therewith, said heating plate consisting of a conductive substrate having one or more thick film resistive tracks formed on a surface of said heating plate.

20 In a sixth aspect the invention consists in a dishwasher comprising:
a wash chamber adapted to accommodate dishes and within which wash liquid is circulated, a rack within said chamber which supports dishes above the floor of said chamber, a rotatable spray arm having liquid discharge nozzles located in the bottom of said wash chamber under said rack, a pump
25 which pressurises said spray arm with wash liquid, and mounting means located centrally in the floor of said chamber which rotatably supports said spray arm, said spray arm in turn comprising a hub portion and two diametrically opposed wing portions extending outwardly therefrom towards the side walls of said chamber, and said wing portions shaped such that they
30 droop downwardly away from the hub portion.

In a sixth aspect the invention consists in a d29. A dishwasher comprising:

a moulded wash chamber adapted to accommodate dishes and within which wash liquid is circulated,

a moulded reservoir tank integral with said wash chamber and sharing a common side wall with said wash chamber,

5 said reservoir tank having a horizontal cross-sectional area much less than the horizontal cross-sectional area of said wash chamber,

an electrically controlled water valve in use being connected to a source of water supply which is arranged to discharge into said reservoir tank, and

10 a syphon means having an inlet in said reservoir tank and an outlet in said wash chamber,

15 said syphon means being positioned at a height such that when water discharged from said valve into said reservoir tank reaches a level corresponding to a predetermined volume of wash liquid, syphonic action takes place to drain said predetermined volume of wash liquid from said reservoir tank into said wash chamber.

In a seventh aspect the invention consists in a dishwasher comprising:

a moulded wash chamber adapted to accommodate dishes and within which wash liquid is circulated,

20 a moulded reservoir tank integral with said wash chamber and sharing a common side wall with said wash chamber, said common wall being capable of transmitting heat from the wash chamber to the reservoir tank and vice versa to thereby form a heat exchanger between said wash chamber and said reservoir tank, and means for transferring water from said reservoir tank to said wash chamber.

25 In an eighth aspect the invention consists in a household appliance comprising:

- 30 a) a wash chamber adapted to receive a load to be cleaned and within which wash liquid is circulated,
- b) a well provided in the floor of said chamber,
- c) an electric motor including:
 - (i) a rotor mounted within said well, and
 - (ii) a stator mounted outside said wash chamber circumferentially to the exterior surface of said well,

d) a wash chamber drain pump including:

an impeller located in said well on the rotor shaft,

said rotor - drain impeller combination held in working positions without mechanical fastenings or restraints such that they may be disassembled simply by lifting them out of said wash chamber.

In a ninth aspect the invention consists in a dishwasher comprising:

a) a wash chamber adapted to accommodate dishes and within which wash liquid is circulated,

b) a well provided in the floor of said chamber,

c) an electric motor including:

(i) a rotor mounted within said well, and

(ii) a stator mounted outside said wash chamber circumferentially to the exterior surface of said well,

d) a wash chamber drain pump including:

an impeller located in said well on the rotor shaft,

e) a wash pump including

(i) a wash pump impeller on the rotor shaft, and

(ii) a spray arm having liquid discharge nozzles rotatably supported in the bottom of said wash chamber for rotation about said wash pump impeller,

said spray arm and rotor - wash impeller - drain impeller combination all held in working positions without mechanical fastenings or restraints such that they may be disassembled simply by lifting them out of said wash chamber.

In a tenth aspect the invention consists in a dishwasher comprising: a wash chamber adapted to receive dishes to be cleaned, a pump for circulating wash liquid within said chamber, a spray arm having nozzles therein which is rotatably mounted adjacent to the floor of said chamber which receives pressurized wash liquid from said pump and dispenses it through said nozzles into said chamber, said spray arm including at least one nozzle of the spray arm which is directed to produce a transverse jet of wash liquid having components tangential to the circular path traced by said nozzle and downwardly, and a drain sump provided in the floor of said wash chamber

having an inlet positioned so as to be directly below and swept by said transverse jet with each rotation of said spray arm.

In an eleventh aspect the invention consists in a dishwasher comprising:
a wash chamber adapted to receive dishes to be cleaned, a pump for
5 circulating wash liquid within said chamber, a spray arm having nozzles therein
which is rotatably mounted adjacent to the floor of said chamber which
receives pressurized wash liquid from said pump and dispenses it through said
nozzles into said chamber, said spray arm having at least one nozzle directed
so as to produce a substantially horizontal and substantially radial jet of wash
10 liquid, and said wash chamber at the height of said horizontal jet having a
peripheral deformation in the corners thereof which acts as a vane to deflect
said jet vertically such that wash liquid is sprayed vertically in areas of the
wash chamber outside the diameter of the spray arm.

In a twelfth aspect the invention consists in a dishwasher comprising:
15 wash chamber adapted to receive dishes to be cleaned, a pump for circulating
wash liquid within said chamber, a spray arm having nozzles therein which is
rotatably mounted adjacent to the floor of said chamber which receives
pressurized wash liquid from said pump and dispenses it through said nozzles
into said chamber, said spray arm having at least one nozzle directed so as
20 to produce a substantially horizontal and substantially radial jet of wash liquid,
and said wash chamber at the height of said horizontal jet having a peripheral
deformation on the planar sections of the walls thereof which acts as a vane
to deflect said jet vertically to produce a laminar flow of wash liquid up said
wall sections and on to the underside of the roof of said chamber such that
25 wash liquid may drip off said roof to thereby come in contact with the upward
facing surfaces of dishes within the chamber.

In a thirteenth aspect the invention consists in a cabinet for a household
appliance of the open sided box type comprising: five side walls rigidly joined
along their edges to leave a substantially rectangular opening defined by the
30 free edges of four walls, and a flange around said four free edges, said flange
on three edges configured as a portal frame with moment resisting corners
and on the fourth edge as a beam linking the ends of the portal frame, the

junctions of the beam and portal frame having no substantial resistance to bending moments.

In a fourteenth aspect the invention consists in a dishwasher comprising:

- (a) a cabinet,
- 5 (b) a wash system slidably mounted within said cabinet in such a manner that it may be withdrawn horizontally out of said cabinet for access thereto, said wash system including:
 - (i) an open top wash chamber adapted to accommodate dishes within which wash liquid is circulated,
 - 10 (ii) a spray generating means for producing a spray of wash liquid within said chamber,
 - (iii) means for evacuating wash liquid from said chamber, and
- (c) a wash chamber lid mounted in the top of said cabinet, which lid is engaged with the wash chamber opening to sealably close off
15 said wash chamber on retraction of the wash chamber.

In a fifteenth aspect the invention consists in a dishwasher comprising a cabinet, a wash chamber within said cabinet adapted to receive washing liquid to effect washing and to receive dishes to be washed, a horizontally disposed rotatable spray arm mounted in a lower portion of said wash chamber and
20 having spray nozzles, a wash pump having an impeller, said wash pump being arranged to draw wash liquid from a lower part of said wash chamber and deliver said wash liquid to said spray nozzles, an electric motor driving said impeller, and the distance between the lowest level of said motor being of the order of 55mm (fifty five millimetres).

25 In a sixteenth aspect the invention consists in an alternating current synchronous motor and starting drive comprising:

a stator including at least one pole pair and windings associated therewith, a permanent magnet rotor having at least one pole pair, sensing means for determining the angular position of the rotor, switching means for
30 energising respective stator windings from the alternating current mains, and a controller which monitors the output of said sensing means and the waveform of the alternating current mains and fires the switching means connected to the stator winding with an appropriate segment of mains half-

cycle which will cause rotor rotation in the desired direction or will increase the speed of rotor rotation.

In a seventeenth aspect the invention consists in a method of manufacturing a stator for a salient pole electric motor comprising the steps of:

- 5 (a) forming a laminated square flux return ring by:
 - (i) providing a continuous strip of workable magnetic material,
 - (ii) cutting notches in one edge of said strip at a pitch equal to the side dimension of said square,
 - 10 (iii) winding said strip edgewise into a square helix by bending the strip edgewise at right angles at each notch, the notches being on the inside of the bend and every fourth notch in registration, until the required stator thickness has been achieved;
- 15 (b) forming salient poles as lengths of magnetic material having end formations complementary to said flux ring notches;
- (c) fitting pre-wound stator coils onto each pole; and
- (d) placing two or four salient poles into each flux return ring such that the salient poles lie in the same plane as said flux ring, extend
- 20 diagonally from the corners of the flux ring, and the end formations lock within the complementary notches in the flux ring.

BRIEF DESCRIPTION OF THE DRAWINGS

Figures 1 to 3 show a selection of ways in which dishwashers according to the present invention can be mounted in modular fashion in a kitchen installation;

Figure 4 is a perspective sketch of a cabinet for a dishwasher according to the invention;

Figure 5 is a diagrammatic cross section of one embodiment of a dishwasher according to the invention showing a wash system partially withdrawn from its cabinet;

Figures 6 to 8 show the dishwasher of Figure 5 between full retraction and full withdrawal and in particular show the wash system drain hose extension;

Figure 9 is a diagrammatic sketch of the water supply system for a single dishwasher module;

Figure 10 is a diagrammatic longitudinal cross section at the rear of the wash chamber showing a reservoir tank having a common wall with the wash chamber;

Figure 11 is a diagrammatic transverse cross section through the reservoir tank;

Figure 12 is a diametrical cross section of the lower part of the wash system showing the spray arm, wash pump, electric motor and drain pump construction;

Figures 13 to 15 show diagrammatically transverse cross-sections of the dishwasher illustrating the filling and emptying modes for the reservoir tank;

Figures 16 to 18 show diagrammatically longitudinal cross-sections of the dishwasher illustrating alternative filling configurations.

Figure 19 is a diagrammatic longitudinal cross section of a dishwasher showing the position of the wash chamber lid;

Figure 20 shows a diagrammatic view of the dishwasher lid and lid lifting mechanism;

Figure 21 is a detailed side elevation of the inner portion of the lid and lid lifter mechanism showing the lid at the start of the closing phase.

Figure 22 is a detailed side elevation of the inner portion of the lid and lid lifter mechanism showing the lid at the completion of the closing phase.

Figure 23 is a graph showing relative displacement of drawer, lid and lid lifter during the closing phase.

Figure 24 is a part plan view of the wash chamber showing one form of means for holding dishes, such as plates, in position;

Figure 25 is a part diametrical cross section of the lower part of the wash system corresponding to Figure 12 showing the water path in detail;

Figure 26 is a block circuit diagram of the electric motor control circuit;

Figure 27 is an exploded view of the major spray arm wash pump and motor components;

Figure 28 is an enlargement of the wash pump impeller;

Figure 29 is an under view of a drain pump impeller;

Figure 30 is a part view of the spray arm and wash chamber wall showing a jet deflecting formation in the corner portion of the wash chamber wall;

5 Figure 31 is a similar view to that shown in Figure 30 but showing jet deflection from straight portions of the chamber wall;

Figure 32 is a waveform diagram of pulses formed by the motor drive circuit;

Figure 33 is a phasor diagram illustrating motor torque monitoring;

10 Figure 34 is a plan view of the underside of a heater plate showing a thick film heating element configuration;

Figure 35 is a perspective sketch of the drain pump and associated inlet sump;

Figure 36 is a perspective view of the bottom of the wash chamber showing a wash water filter jet cleaning system;

15 Figure 37 is a diametrical cross section through the wash system showing the wash filter jet cleaning system;

Figure 38 shows a horizontal cross section through the wash chamber drain so as to show the major wash system components even although they are mounted one above the other and are separated by partitions.

20 Figure 39 is a detail of part of the wash chamber floor showing a helical drain channel;

Figures 40 and 41 show diagrammatically two options for water hose connections two modular dishwashers forming a composite pair,

Figure 42 shows an isometric view of the motor stator,

25 Figure 43 shows a portion of the blank lamination material prior to formation as the stator of Figure 42, and

Figure 44 is a plan view of a blank for forming the cabinet of Figure 4.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

30 In the preferred embodiments the dishwasher is constructed with a height dimension approximately half that of conventional front-loading domestic dishwashers. It is intended to be used alone or as one of a number, more usually one of a pair of such dishwashers.

Referring to figures 1 to 3, various installation concepts using one or two dishwashers according to the present invention are shown. It is a concept of the present invention to provide a modular dishwasher unit. In Figure 1, two such dishwashers 2 are shown stacked one above the other under a sink bench 1 which will typically be between 850 and 900mm above floor level. In Figure 2 two dishwashers 2 are shown mounted one on either side of a sink forming part of the sink bench 1. In Figure 3 only a single dishwasher 2 is provided under a sink bench 1. Because of the reduced height dimension a dishwasher according to the invention could be bench mounted. Thus each dishwasher 2 can be regarded as a modular unit which is an independent self contained dishwasher capable of accommodating any conventional dish load.

From Figure 1 it can be seen that when two modular dishwasher units 2 are stacked one above the other the configuration is similar in external dimensions to conventional dishwashers. Two modular units 2 installed side by side immediately under a bench top as in Figure 2 offer the same capacity as a conventional dishwasher but avoid the inconvenience of a user having to bend down to reach the lower half of the dishwasher. Additionally access is improved in that a wash chamber 3 (see Figure 5) may be slidably withdrawn from the cabinet 4 of a dishwasher unit by being mounted in the form of a drawer.

Some modular pair arrangements could be manufactured as such rather than pairing two individual modules at installation. For example the configuration shown in Figure 1 could be paired at a maintenance to mechanically link the individual dishwasher cabinets. In such an arrangement there would be advantage in combining the plumbing arrangements as will be discussed later in this specification.

The provision of two independent dishwashers allows for considerable flexibility in operating modes.

1. One module operating, or two modules operating simultaneously with a mixed dish load. With each module capable of accommodating the largest item of dish load, this concept offers an increased capacity for large items.

2. One or both modules operating, but not necessarily simultaneously, where each module has either lightly soiled or heavily soiled dish load, and the appropriate wash programme set to suit the individual module.
 3. One module being gradually filled with soiled dishes, while the second module is being emptied only as its clean dish load is being reused. For reasons of hygiene this is not practical with single dishwashers
 4. One module programmed for lightly soiled loads and the other module for heavily soiled loads.
 5. One module switched on as soon as it has been filled with soiled dishes.
- That is, smaller loads may be efficiently washed.

Cabinet Construction

Referring now to Figure 4, in the preferred form the present dishwasher cabinet is constructed from sheet metal to form a five sided box structure having a top 5 a bottom 6 and sides 7 and 8 and back (not shown). The open front of the cabinet 4 is flanged as a portal frame having two portal members 10 and 11, these portal members decreasing in depth from the corners 12 and 13 to the extremities 14 and 15 and decreasing along the bottom face to a central joint 16. This enables an adequate sized opening to be provided in the cabinet while at the same time provides adequate stiffness to the front of the cabinet. This technique overcomes the rigidity problem presented by any open sided box structure and could be used in many applications beside dishwasher cabinets. The portal frame members 11 and 12 are jointed together at 16 by a very thin section of metal which in structural terms comprises essentially a pin joint. Similarly, ends 14 and 15 of the portal members are effectively joined to flange section 18 by pin joints. This section effectively forms a beam to tie together the ends of the portal members. Unlike the conventional application for portal frames joint 16 is not subject to any significant load normal to panel 6. The function of the portal frame in the present application is to provide bracing against transverse loads and there is no requirement or advantage in having joint 16 moment resisting.

The portal could be inverted but the orientation shown assists in allowing clearance for a drain pump to be described later. It also means the portal

frame profile substantially follows the profile of the wash chamber which itself is shaped so as to optimally hold large plates.

Drawer and Connections to Wash System

One aspect of the present invention is that a dishwasher is provided whereby
5 the wash chamber in which dishes are placed, together with all other components necessary to the wash system, is mounted within a cabinet on slides to function as a drawer. This configuration is shown in Figure 5 where a wash chamber 3 is shown slidably mounted within cabinet 4 in a partially withdrawn position.

10 An aesthetically pleasing facia 20 is fitted to the front of wash chamber 3 and incorporates a drawer pull (not shown). When fully retracted or closed (as shown in Figure 6) facia 20 abuts the front of the cabinet 3.

A dishwasher as described is intended for installation in an open cavity, usually under a bench, so that the facia 20 effectively closes off the cavity and
15 is the visible component of the dishwasher in the same manner as with conventional front loading dishwashers

Unlike the cabinet wash chamber 3 preferably formed as a one piece plastics moulding. This has obvious advantages over sheet metal fabrication.

The use of a drawer configuration means that flexible and extending cable
20 and hose arrangements are required for running between the cabinet and the wash system. Electrical connections for the drawer mounted components could be provided by a socket 31 attached to the cabinet and a plug 32 attached to the washing chamber. Connection is made when the drawer 17 is in the substantially fully home position. Preferably, however, fixed wiring is
25 employed using a flexible cable loop. In this form the electrical cable could be attached compositely to the drain hose shown in Figures 6 to 8.

Water connections to and from the sliding washing chamber 3 are arranged as follows. A drain hose 35 (Figures 6 to 8) is formed in a loop and is arranged to have a central portion 36 transverse to the direction of
30 movement of the chamber with two arms 37 and 38 connected to the central portion. As may be seen by comparing Figures 6, 7 and 8, the drain hose arms 37 and 38 bend where they are connected to central portion 36 so that the two arms move from a position in substantially the same plane (orthogonal

angles to the direction of movement of the drawer 17) as shown in Figure 6 to the position shown in Figure 8 where the two arms are more or less in the same plane but at right angles to the position shown in Figure 6. This arrangement minimises the space required to accommodate the drainage hose when the wash chamber is in the closed position.

The water supply management for the wash system is shown in Figure 9. A wash hose 40 connects between a discharge spout 53 and an electrically operated water valve 51. Valve 51 could be a solenoid valve, for example. Valve 51 is in use coupled to a household wash supply tap 46. The valve 51 is moulded to the hose 40. In addition an electrical cable is also moulded to hose 40 to provide an electrical connection to valve 41. The electrical connector 47 is attached to a cable tail 47 allowing connection to the dishwasher controller through a cabinet mounted socket.

Water Reservoir Tank

Wash water is supplied to a reservoir tank 33 which is partially integrally formed with the wash chamber 3 (see Figure 10). The chamber 3 has a closed flange on one end wash. A moulded plastics cover member 44 is welded to the flange dry line for form the tank 33. The tank 33 shares a common wall 34 with the wash chamber. The use of a separate tank of much smaller horizontal cross section than that of the wash chamber 3 allows accurate metering of the volume of water used for washing. This is especially important where, as here, a relatively small change of water is used - typically 2 litres.

The manner in which the reservoir tank 33 is used to meter water into the wash chamber will now be described with reference to Figures 11 and 13 to 15. The water supply hose 40 is shown connected to electrically actuated inlet valve 51 fed from a supply of cold water. The water supply hose terminates at a spout 53 fixed to the cabinet 4. Spout 53 discharges into tank 33 only when wash chamber 3 is in the closed position. Alternatively a flexible hose 52 (Figure 18) may be connected from the cabinet 4 to a spout 54 fixed to the tank 33. In either case inlet valve 51 cannot be opened unless the wash chamber 3 is in the closed position. An interlock switch can be provided to accomplish this or the electrical connection broken in the manner discussed above in relation to Figure 5.

Control of the filling of tank 33 is determined by a water level sensing means 60 having a permanent magnet in a float 61 which is able to activate reed switches 62 and 63. Inlet valve 51 is opened and the tank is filled to a level such that the float 61 rises and activates the lowest level reed switch 62 to cause the inlet valve 51 to be closed as indicated in Figure 14. Water is held in tank 33 for a variety of purposes which will be described, but when required discharge into the wash chamber 3 occurs as follows. Inlet valve 51 is again opened to raise the water level to a level just above the top of the loop of a syphon tube 55 whereupon syphonic action occurs causing the entire contents of the tank to be dumped into the wash chamber 3 through syphon tube outlet 57. Upper reed switch 63 senses when the water level rises above the top of syphon tube 55 and the inlet valve 51 is then closed. The flow rate of the water through valve 51 must exceed the syphon flow rate for switch 63 to be triggered.

Alternative methods may be used to switch valve 51 off as soon as syphoning occurs. A sensing means can be included in the discharge leg of the syphon 55. Alternatively reed switch 63 can be located below the level at which syphoning occurs and the time taken to increase water level from reed switch 62 to reed switch 63 used to calculate flow rate of the water supply. A further calculation can be made to determine the additional time required for the water level to reach that required for syphoning. Inlet valve 51 can be switched off after expiration of this calculated period of time.

Tank 33 shares a common wall 34 with wash chamber 3 as is best seen in Figure 11. This wall is thermally conductive and constitutes a heat exchanger between the wash chamber and reservoir tank. The plastics material used for the wash chamber may itself be sufficiently conductive to obtain adequate heat transfer or alternatively a metal wall insert can be fitted. When tank 33 is filled prior to use for washing or hot rinsing the water will be pre-heated due to heat transfer from the heated water and interior of the wash chamber. On the other hand the cold water in the tank will tend to keep wall 34 cooler than it would otherwise be and this phenomenon is used during the drying cycle as described later.

In summary the reservoir tank 33 configuration provides:

- (a) a container in which the inlet water volume can be measured above,
- (b) a means of cooling a surface of the wash cavity so that the steamy air inside the wash cavity, at the completion of a wash programme, can condense and thereby allow the wash load to dry,
- 5 (c) a heat exchange so that the incoming volume of inlet water can be pre-heated prior to entering the wash chamber to thereby remove the risk of thermal shock to the washload if it is at an elevated temperature, and
- (d) reduced heat up time when the liquid is transferred to the wash chamber and pre-heating occurs while the wash system is operating to thereby
- 10 reduce energy usage.

[Plumbing refer Figures 40 and 41]

When two dishwashers are used in combination in the manner previously outlined they are nevertheless plumbed so as to share household fittings during installation. Two alternative methods of providing water supply are

15 shown in Figures 40 and 41 respectively. In Figure 40 each dishwasher water supply hose 40 is terminated on a respective outlet of a dual valve 51 which is coupled to a cold water tap. Each section of the valve is controlled separately by respective controls in the two dishwashers. In Figure 41 the water hose 40 for the top dishwasher is connected to a two-way or shuttle

20 valve 48 which also supplies water to the spout 53 of the lower dishwasher. Valve 48 receives water from valve 51. Valve 48 operates to divert water between the top and bottom washers.

Wash Chamber Lid

Because in the preferred form of the invention wash chamber 3 (and

25 associated wash system) is arranged as a sliding drawer 17 (see Figure 19) dishes are top loaded and a watertight lid 66 provided. Lid 66 is mounted in cabinet 4 rather than the wash chamber 3 and engages with the top of the wash chamber only when the drawer 17 is fully closed. Thus when the drawer is withdrawn the lid is left in the cabinet. The user has no direct involvement

30 with opening and closing the lid. A lid lifting mechanism is provided to raise and lower the lid as the drawer is opened and closed, and to lock the lid down in place when the drawer is fully closed.

The lifting mechanism includes a sub frame 24 mounted by four link members 26 hinged at 27 to the sub frame 24 and hinged at 28 to a frame member 29 forming part of the cabinet 4. The links and hinges are preferably formed as a unitary moulded polypropylene or "living" hinge. Lid 66 is floatably retained by the sub-frame 24A tension spring 30 biases the sub frame 24 and lid upwardly to a position in which the lid 66 is lifted away from the to of wash chamber 3. Figure 21 shows the chamber 3 almost fully retracted at the point of lid closure. An abutment flange on chamber 3 (moving to the left) has made contact with lid 66 and contact with a portion of lid lifter 24. Further leftward movement of chamber 3 will cause lifter sub-frame 24 to rotate link 27 anti-clockwise, moving the sub-frame and lid both inwardly (to the left) and downwards. The relative displacements of the chamber (drawer), lid and lid lifter are shown graphically in Figure 23. On that graph abutment of the moving parts occurs at point A and further retraction of the chamber to point B results in the lid and lifter moving inwards (increasing value of x) downwards so that the lid clamps onto to top of the open wash chamber. Provision is made for locking the lid in this position. Further retraction of chamber 3 causes the abutment flange to ride up over the abutting portion of sub-frame 24 (which does not move further) and together with the lid 66 (which is free to slide within the sub-frame) moves to point C on the graph, being the physical position shown in Figure 22. The lid and chamber flange in this "home" position are clamped together. Buffers 21 damp the travel between points B and C.

Wash Chamber Dish Supports

The positioning of dishes in the washing chamber 3 is facilitated by providing a rack 70 on the bottom of the washing chamber. Slots, notches or other details 71 may be provided on at least one side wall of the washing chamber 3 as shown in Figure 24. These details may be moulded in the washing chamber wall which is preferably a moulding of a plastics material and the arrangement is such that larger dishes for example plates and other dishes having a rim can be supported against the washing forces operating. Preferably a rack providing more conventional dish support may be used to support dishes, although in the present invention such a rack is fixed rather

than slidable. However the rack must be configured to optimise the space available in the wash chamber and in this respect must allow the bottom edge of dishes (such as plate 200) to extend below the spray arm hub as shown in Figure 12.

5 **Wash System Rotating Parts**

Referring to Figures 12 and 25 the washing chamber 3 has a spray arm 75 having spraying apertures or nozzles 76 in an upper surface thereof. A wash/rinse water pump 77 is rotated by an electric motor 78 and preferably this motor also rotates a drain pump 79. The inlet 85 to the wash pump 77 is
10 fed by an annular passageway or plenum 80 under a filter plate 104 having an annular inlet comprising a series of apertures 81 at its periphery. The floor 82 of the wash chamber moulding 3 is recessed to provide the plenum. The spray arm 75 is symmetrically curved as shown with the outer ends 86 curved downwardly from the central or hub portion 121. The purpose of this
15 curvature is so that larger dishes (such as plate 200 shown in Figure 12) can be accommodated within the low height of the wash chamber 3.

Because of the low volume of water change used for each wash/rinse cycle (2 litres) only a low suction head is available for wash pump 77. This means only a small pressure drop can be tolerated which means the pump
20 velocity intake must be low. To achieve this a large water intake area is required.

As a result of the wash pump requirement for a large intake area, in order to successfully operate with a low liquid volume and a minimal suction head, the height available to incorporate the system that filters the wash liquid
25 prior to it entering the wash pump inlet is reduced as compared with conventional dishwashers.

As already mentioned the intake area is covered with a filter comprising an annular ring of apertures 81 (in filter plate 104) of approximately 350mm outside diameter and 300mm inside diameter. To ensure that this perforated
30 area remains as clear as possible for the liquid to flow through, an active filter cleaning system is used. Referring to Figures 36 and 37, one or more jets 150 are provided in the spray arm 75 to create a clearing effect on the filter plate 104 ahead of the spray arm as it rotates.

Large soil particles 153 are cleared off the perforations radially onto and against a circular recess 152 and rotated around the filter plate to drain sump 134 which is provided with a passive filter or strainer 151. As with filter systems found in conventional dishwashers, the strainer 151 will require regular servicing by the user. As shown in Figure 36 the strainer 151 has a "mouth" configuration to scoop in the soil being cleared by jets 150.

The arrangement of the spray arm, wash pump, motor and drain pump can be understood with reference to Figure 25 and to the exploded view of Figure 27. Spray arm 75 integrally includes the wash pump casing 87 which has two delivery volutes 88 and 89 leading to outer sections 84 and 86 of the spray arm respectively. The junctions between the casing 87 and the outlets 88 and 89 are preferably of tangential volute formation as shown in Figure 27. To ensure wash liquid pressure is available in the inner sections of the spray arm volute surfaces 88 and 89 are stopped short of making contact with the edges of the spray arm. This allows liquid to flow back towards the inner sections to provide pressure for nozzles 90 in this section.

The wash pump impeller 95 (shown in more detail in Figure 28) has blades 96 curved forwardly at their lower edges. Because in the preferred form the motor 78 is a permanent magnet, synchronous AC motor, it is important that the motor starts under no load conditions. To achieve this the static water level in the wash cavity is set to just touch the bottom of the wash pump impeller. This is indicated by the water level symbols in Figure 25. However, the centrifugal type pump employed is not self priming. It is for this reason that the impeller 95 has the axial flow type forward facing blade sections 97 on the bottom of the blades. After the motor has started under no load, the leading edges 97 of the impeller lift the liquid and the pump will prime and operate normally. These leading edges 97 also benefit the systems when the motor is rotating in the drain direction (reverse to wash direction). The now backward facing blades resist picking up the liquid and the wash pump cannot operate.

The motor rotor 100 (figure 27) is formed using a ferrite permanent magnet embedded in a plastics casing and has a splined shaft 99 to engage and drive wash pump impeller 95. The motor rotor 100 incorporates on its

lower plastics surface also an impeller 101 for the drain pump. A cross section drain pump is shown in Figure 29. Impeller 101 has blades 102 shaped as shown so that when the motor rotor is rotated in the direction of arrow 103 the drain pump will drain liquid from the washing chamber as will be described more particularly later. When the motor rotor is rotated in the opposite direction (see arrow 104) to operate the wash pump the drain pump is substantially prevented from pumping due to the de-optimised profile of the impeller and casing when rotating in this direction. There is also a non-return valve provided in the drain pump outlet 109 to stop flow being drawn out of the drain hose into the wash chamber.

To prevent water flow by-pass around the rotor and into the wash chamber when the drain pump is working a shallow plastics impeller 105 is formed on the top surface of rotor 100. The eight impeller blades are about 1.5mm in height. This creates a counter flow in the drain direction. This hydrodynamic seal acts only against liquid flow by-pass. It does not prevent air bleeding from the drain pump as it primes. It will be appreciated that apart from hygiene reasons drain water back flow would cause abrasion of the rotor and contamination of the spray arm nozzles.

The drain pump casing 106 (Figures 25, 27 and 35) is formed by providing a close tolerance well in the floor of wash chamber 3. It is open at the top to the wash chamber 3. This well could be moulded into the floor or moulded separately and fitted later. The motor rotor 100 mounts within casing 106 on shaft 107. It is a feature of the invention that the motor rotor 100 is located within the wash chamber and submerged in washing liquid. The motor stator 111 (see also Figure 38) is located outside of the wash chamber and separated from the rotor by drain pump casing 106. The stator in the preferred embodiment comprises four salient poles 110 to make up a two pole pair (110a and 110b) stator. The drain pump casing 106 has a drain pump inlet 108 and a drain pump outlet 109. The arrangement shown in Figures 25 and 27 is such that disassembly of the wash system is very simple. The spray arm may be removed simply by lifting it off its bearing 115. The motor rotor 100 and the associated wash pump impeller 95 may be lifted from the well 106 by lifting the filter plate 104. Thus substantially all the working parts can be readily

removed to enable cleaning of the drain pump casing 106. No fastenings are needed to retain these components in their working positions. A similar arrangement could be used in appliances other than dishwashers, for example clothes washing machines.

5 A preferred form of drain sump 134 (shown in Figure 27 and diagrammatically in Figure 35) is arranged in the wash chamber base 82 so that substantially all liquid in the washing chamber will drain into it. The drain pump inlet 108 is connected to a lowest part of the sump 120. To further improve wash liquid drainage into sump 134 the floor of the wash chamber is
10 provided under the filter plate with a helical channel 160 having its lowest point 161 opening into the sump 120 as shown in Figure 39.

It is important to achieve the modular advantages earlier outlined that the construction of the motor-pump combination is such that the height of the wash pump and electric motor from the highest level 121 of the spray arm 75
15 (Figure 25) to the lowest level of the electric motor is very small - typically of the order of 55mm. The height dimension including the drain pump casing extending below the motor is 75mm.

Referring to Figure 30, a nozzle 116 may be provided in the ends 86 and 84 of the spray arm 75. This provides a substantially horizontal jet of wash
20 liquid 117a. The corner portions of the wash chamber wall in the plane of the jet have a shaped protuberance 118 to form deflecting vanes to deflect jet spray 117a into a substantially vertical jet 117b. This ensures vertical spray coverage in the chamber corners where rounded corners of only small radius are used well outside the spray arm diameter. In Figure 30 a glass 201 is
25 shown accommodated in a corner of the wash chamber benefiting from the deflected spray.

Water Heater

The wash cycle requires the use of hot water and it is necessary to provide a heater for heating the cold water supplied to the dishwasher to an
30 elevated temperature.

In the present invention the water heater is provided in the floor of the wash chamber as shown diagrammatically in figures 25 and 34. The heater is formed by a circular metal heating plate 141 which has resistive heating

elements 142 in intimate thermal contact therewith on the underside. The heating plate 141, which is about 250mm in diameter, forms the central portion of the wash chamber floor and is sealably mounted in a circular aperture 143 provided in the floor. The heater plate in turn has a central aperture 144 which accommodates well casing 106 which houses the motor rotor 100 and drain pump 101. Seals 145 and 146 respectively seal the heater plate sump and floor junctions.

Heater plate 141 is formed from porcelain enamelled steel. A pattern of resistance elements 142 is formed on the enamelled lower or exterior surface of the plate. These elements are fabricated using thick film technology where a resistive paste or ink is deposited or printed on the enamel substrate in the desired track pattern and then fused solid. The tracks may be made up of conductive and resistive portions. Power connections to the heater are made to conductive, non-heating portions 147 of the tracks. When energised the resistive tracks dissipate heat which is conducted to the steel plate and thence to the liquid in contact with the opposite surface of the plate. Temperature sensors may also be formed on the plate using thick film techniques to provide feedback for temperature control circuitry. The wash pump loading can also be monitored to provide an indication of flow and the heater switched off on detection of inadequate wash liquid flow. The thick film technology used can also provide thermal oven temperature protection links, inter-connections to the motor, and a termination point for connection to the motor stator windings.

The heater plate provides a relatively large surface area (compared to conventional tubular sheathed elements) for heating the wash liquid which during the wash cycle will flow across the top surface of the plate. A heater of this configuration provides low power density heating and low surface temperature which improves safety and minimises the risk of thermal damage to adjacent plastics components.

In the preferred form the heater plate is disposed substantially horizontally in the wash chamber floor which makes it simple to ensure a constant substantially laminar flow of wash liquid is passed over it. However, it would be feasible to mount the heater plate vertically and locate it in one of

the side walls of the wash chamber, although not wall 34 which is common to tank 33.

Motor and Motor Drive

Control of the filling, rinsing, draining and washing cycles is provided by
5 a programmed microcomputer 120 (see Figure 26) for example a National Semiconductor COP881C user operated microprocessor console 126 connects to the microcomputer. The water inlet valve 51 already referred to connected to an output of microcomputer 120.

A primary function of the microcomputer 120 is control of the start up
10 and running of synchronous motor 78, both for washing in one rotational direction and draining in the other direction.

Motor 78 is an alternating current synchronous motor with the stator field created by windings on one or more pole pairs. Referring to Figures 25, 27 and 38 in the preferred form one pole pair 110a of the stator 111 is
15 geometrically displaced 90° to the other pole pair 110b. The current in one pole is phase shifted in relation to the mains current in the other pole. The permanent magnet (not shown) in the rotor 100 has two poles, aligned diametrically. The magnet rotates synchronously with the stator field, with an angular relationship to the stator field determined by the load.

Being an AC synchronous motor, a starting method is required to bring
20 the rotor to synchronous speed in a required direction. A drive circuit which provides commutation to achieve this is shown in Figure 26. Corresponding wave form diagrams are shown in Figure 32. The mains voltage polarity is monitored by polarity detector 127 and the magnet position is monitored by
25 means of back EMF sensing in the stator windings 128 and 129. Comparators 123 and 124 detect back EMF zero crossings. The outputs of comparators 127, 123 and 124 are indicted by wave forms 32(b), 32(d) and 32(g) respectively. Other sensors (rather than back EMF) could be used such as optical or Hall effect sensing. The stator windings are switched across the
30 single phase AC supply by triacs 121 and 122 respectively as will be described. Switching is controlled by programmed microcomputer 120. The running direction of motor 78 is determined by startup commutation algorithm stored in the microcomputer. This algorithm compares instantaneous mains

polarity (waveform 32(b)) with instantaneous rotor magnet position (waveform 32(b) or 329g)). The algorithm provides gate pulses (waveforms 32(e) and 32(h)) to the triacs 121 and 122 only if the resultant torque which would be produced is in the required direction. The triacs of course, once turned on, will remain on until current through each device is zero. The resultant stator winding currents are shown as waveforms 32(f) and 32(c), phase shifted in relation to the respective gate signals.

The back EMF signal may be derived from the non-energised stator windings. It should be appreciated that the drive technique disclosed involves simply taking power from the mains at points in the mains cycle when a pulse of power would be beneficial for rotation of the motor. There is no attempt to synthesise commutation waveforms from a direct current supply derived from the mains.

When the microcomputer determines from back EMF zero crossing frequency that the rotor speed is close to synchronous with the rotating stator field the motor is switched to run directly from the mains as a split phase motor without any need for electronic commutation. It will be appreciated that during electronic commutation only one stator winding is energised at any one time and this limits the motor power. For synchronous running triac 121 remains ON to connect winding pair 128 across the mains while triac 122 is switched OFF. At the same time triac 123 is switched ON to energise winding 129 pair via resistor-capacitor network 133 which applies a 90° lagging current to that winding pair.

To enable the motor to run over the range of input voltage and output power required, a method of limiting input power to the motor is applied. This is achieved by switching the triac 121 to phase angle cut the supply to stator winding 128, so regulating the current magnitude and hence controlling motor input power.

With a motor and motor control system as described motor torque can be monitored to infer wash pump and drain pump mode conditions such as: (i) wash pump operating normally, (ii) wash pump ventilating, (iii) low or nil water in the system, (iv) foaming of the wash liquid occurring, (v) wash pump

blocked or stalled, (vi) drain pump operating normally, (vii) all liquid pumped out in drain mode and (viii) drain pump blocked or stalled.

The motor torque is monitored as follows. Referring to Figure 33 each pole pair winding 128 and 129 has voltage and current values referred to as V_a and I_a and V_b and I_b . When the microcomputer compares the value of the relationship between these two phase angles with a range of pre-determined values, the degree of potential torque output of the motor at that time, can be determined.

When the motor runs in the reverse direction for draining, the start up method is unchanged. However, when synchronous or near synchronous speed is detected, and run mode is selected, only one set of poles continue to operate - that is, the motor becomes a single pole pair motor. The additional complexity required to run on both pole pairs in the reverse direction is unnecessary as less power is required to operate the drain pump. The motor run mode for the applications described does not involve commutation from the drive circuit, but in other low power applications the motor could be permanently commutated by the drive circuit. The configuration of the motor stator can be seen in Figure 27. Two orthogonal salient pole pairs 110a and 110b carry windings 128 and 129. The pole taps lie on a common circle of a radius slightly greater than the drain pump casing or well 106. The salient poles are made of motor grade iron laminations in a conventional manner.

The flux return path for the salient poles is provided by a laminated iron ring 125. This ring also helps to structurally support the salient poles which are shaped at their extremities to "dovetail" into appropriately shaped recesses 156 in ring 125.

Ring 125 is made up by stamping a continuous length of laminating strip (see Figure 43) with recesses 156 to provide for salient pole dovetails and bending into the square ring configuration shown in Figure 42. The blank stator material is edgewise wound in helical fashion to form a stack of laminations of the desired thickness with the square configuration shown and recesses 156 in each corner for dovetail engagement with the salient poles.

In use on the dishwasher the stator is filled under the wash chamber floor so the salient poles engage circumferentially about well 106 and this line up

with the permanent magnet rotor 100 mounted within the well. A very low height pancake shaped motor is able to be formed in this matter with the advantage that no dynamic shaft seal with the wash chamber is required due to the rotor being mounted inside the well and separated from the stator by the thickness of the well walls which lie in the motor air gap.

Operation

The operation of a dishwasher according to the present invention is as follows. The drawer 17 is withdrawn from the cabinet 4 and dishes stacked in a rack within the washing chamber. The drawer 17 is then closed and lid 66 simultaneously seals against the top of the wash chamber 3. Microcomputer 120 then initiates the manually chosen cycle of operations. Inlet valve 51 is opened causing the water tank to fill to the level shown in Figure 14 i.e. just below the loop of the syphon tube 55. The inlet valve is again opened and tank 33 filled until syphoning occurs whereupon the inlet valve is closed. The controlled volume of water discharged into the wash chamber 3 may be used for rinsing or washing, as selected. If rinsing washing is required the electric motor 78 is switched on to rotate in the appropriate direction to cause the wash pump 95 to operate. As a result of the wash pump casing being formed by part of the spray arm there is a reaction between the pump impeller and the spray arm causing the spray arm to rotate by partial fluid coupling. At the same time the wash pump causes discharge of water from the spraying nozzles 76. After spraying the soiled water returns to the lower part of the washing chamber, passes through the apertures 81 in the filter plate and is drawn through the passageway 80 into the wash pump to be recirculated.

The wash cycle is substantially similar to the rinse cycle except the water in the wash chamber will be heated during activation of the wash pump.

When a cycle of washing has been completed, for example, a cold rinse, the electric motor 78 is stopped and its direction of rotation reversed. As a result the drain pump impeller 101 is operated to drain rinse water from the wash chamber through the hose 37 for delivery to waste. After drainage has been completed, refilling of the washing chamber takes place in the manner described.

At the completion of the wash programme the drying cycle commences. Water on the dishes is vaporised by the residual heat in the wash chamber and load. The tank 33 is filled with cold water 119. The common wall 34 will cool and water vapour in the chamber 3 produced after the final hot rinse condensed thereon. This obviates the need to vent hot water vapour from the dishwasher. When the drying cycle is completed the drawer 17 is opened and the dishes removed for storage or for use as desired.

Detergent may be dispensed into the washing chamber by use of a detergent dispenser such as that disclosed in either our New Zealand Patent Specification 234271 dated 27 June 1990, or preferably our New Zealand Patent Specification 238504 dated 12 June 1991.

By way of example only a typical wash programme for a moderately soiled load is set out below:

- 1) Dishwasher loaded, programme selected and switched on.
- 15 2) Controller turns on inlet valve and syphon starts and tub fills (tank already fill up to pre-syphon point from previous use).
- 3) Wash pump starts for a cold pre-rinse. No heating occurs. 3 minute duration.
- 4) Wash pump stops, motor reverses and pumps out wash liquid.
- 20 5) Tub refills and wash pump re-starts for main wash. Heater switches on, until temperature reaches 65°C. At 45°C the detergent dispenser releases its detergent.
- 6) When 65°C is reached, heater turns off. Washing continues. Tank fills to pre-syphon point and is pre-heated by the hot wash liquid in the tub.
- 25 7) After 5 minutes after reading 65°C, washing stops, motor reverses and drains tub.
- 8) Tub fills with pre-heated liquid, for first post rinse. No heating this rinse. Tank refills to pre-syphon point and pre-heats.
- 9) After three minutes washing stops, liquid pumped out, pre-heated liquid fills tub.
- 30 10) Final rinse begins, with heater up to 65°C. At 55°C rinse aid is dispensed.
- 11) At 65°C final pump out occurs.

12) At completion of pumpout, tank refills to pre-syphon point and drying cycle commences.

13) After approximately 30 minutes, wash load is ready for removal if desired.

5 This programme has a duration of approximately 35 minutes and water usage is 8 litres of water.

ADVANTAGES

The dishwasher of the present invention, at least in one or more preferred forms, has the following advantages:

1. Motor:

- 10
- The permanent magnet rotor runs in the wash liquid thereby precluding any need for contacting dynamic seals to contain liquid in the system.
 - The permanent magnet, synchronous type motor is a comparatively high efficiency motor which does not require forced cooling.
 - The chosen pole configuration allows for the shallow height of motor (in

15 the axial direction).

 - Simple and reliable electronic starting method.
 - The motor operating principle and self monitoring system ensures constant, synchronous operation. If asynchronous running is detected, the motor will stop and restart automatically. The motor has two pole

20 pairs to achieve the high torque required and has the second set of poles capacitor shifted 90° to minimise the electronics required.

 - When running in reverse, the motor uses one pole pair to also reduce the electronic componentry required.

2. Washpump/Spray Arm:

- 25
- The placement of the wash pump inside the spray arm removes the need for any of the conventional pipework connecting the two devices. This means that there is practically no 'dead' volume in the system, minimising the liquid volume required for the pump to operate.
 - Also, this absence of pipework means losses are minimised i.e. high

30 hydraulic efficiency.

 - Spray arm rotation is created by the partial fluid coupling between the wash pump impeller and the pump volute. Rotation speed adjustment can be made by using a small degree of reaction from jets. Normally in

prior arrangements the pump is a separate unit situated below the sump and connected to the spray arm by means of pipe work. Some dishwashers have the pump housing as part of the sump. Such systems are disadvantageous for the following reasons.

- 5 a) The vertical space requirement of a separate pump and spray arm precludes the possibility of designing an extremely compact dishwasher.
- b) The often complicated pipe work accounts for inefficiencies through friction losses.
- 10 c) The plumbing between the pipe and spray arm is a dead volume for washing liquid and opposes efforts to reduce liquid consumption.

The present invention at least in the preferred form, is aimed at overcoming these disadvantages and providing the following further advantages.

- 15 a) A pump and spray system wherein centrifugal type pump is mounted integrally with a rotating spray arm. The pump discharges the wash liquid directly into the arms of the spray arm without intervening plumbing.
- b) The compactness of pump and spray system facilitates maximal usable space within a given dishwasher height or for a given load capacity thus promoting the design of compact dishwashers.
- 20 c) Because there is no pipe work between the pump and the spray arm and hence no frictional losses the overall efficiency is vastly improved compared to conventional systems. This results in smaller power requirements for the motor.
- 25 d) Because of the lack of pipe work there is an absolute minimum volume in the system requiring filling before the system operates which facilitates low water usage and reduced energy consumption.
- e) By virtue of the fluid coupling between the pump impeller and the pump housing, power to rotate the spray arm is transmitted from the
30 impeller to the spray arm. Therefore conventional reaction jets which may be used but are preferably not used, use additional wash liquid and do not usually contribute to the wash action.

- f) It is possible to produce the complete pump and spray system in two parts, one being the spray arm pump housing and the other being the pump impeller, the system is therefore intrinsically simple.
- g) Should the pump malfunction because of a blockage, lifting off the spray arm exposes the impeller and other parts for cleaning.
- h) Separate bearing systems for a pump and a spray arm are avoided.
- i) Rationalisation of parts reduces manufacturing costs.
- j) As no connections are necessary between the pump outlet pipe work and spray arm which are usually outside the dishwasher tub the potential of leaks in this area is removed.
- To enable the washing pump to operate without ventilating (pumping air) and with only minimal suction head available, a large intake area for the pump is employed. The pump intake is an annular area at approximately 300mm diameter and approximately 7mm high. This allows for a pump performance in the range of 65 litres/minute at a head of 2 metres that requires only 2 litres of liquid in which to operate.
 - The wash pump impeller is of the mixed flow type, with a radial centrifugal outlet and an optimised axial flow inducer at the inlet. This inlet inducer benefits the pump priming in the wash mode and helps prevent the spray arm volute priming when in the drain mode. The drag created by the wash pump in the drain mode is also reduced by the inlet inducer. Both these benefits reduce the drain mode power requirements, aiding the motor running on one pair of poles - as a result of the improved priming ability of this pump, the wash pump intake is successfully located below the wash pump housing.
- 3. Drain Pump:**
- The drain pump impeller is an adaptation of a paddle type pump that is optimised in such a way that the maximum pumping performance is achieved in the drain mode, yet the opposite direction i.e. wash mode, no pumping occurs and low drag is generated.

The low drag generated when the drain pump is operating in reverse means that there is maximum motor power available to drive the wash pump.

- The drain impeller detail is moulded integrally with the motor rotor.
- 5 ● The drain pump housing is integral with the motor housing and central plain bearing for the rotor.
- Should the drain pump become blocked, jammed or require any servicing it can be accessed by removing the spray arm 75, the filter plate 104 which will also lift the motor rotor 100 off its bearing shaft 99,
- 10 revealing the drain pump housing 100 which also forms the rotor housing.
- Upon drain pump startup, any unwanted air present in the drain pump can escape up between the motor rotor and the motor housing. To check the flow of wash liquid through this path after the air has been
- 15 passed, a centrifugal pump impeller detail is moulded on the top face of the motor rotor which in effect opposes the flow of any liquid trying to escape.

WE CLAIM:

1. A dishwasher comprising:
 - a) a wash chamber adapted to accommodate dishes and within which wash liquid is circulated,
 - 5 b) a well provided in the floor of said chamber,
 - c) an electric motor including:
 - (i) a rotor mounted within said well, and
 - (ii) a co-acting stator mounted outside said wash chamber on the exterior surface of said well, and
 - 10 d) a wash pump having an impeller driven by said rotor.
2. A dishwasher as claimed in Claim 1 further comprising
 - a) a wash chamber drain pump including:
 - (i) an impeller located in said well together with said motor rotor, said impeller being driven by said rotor,
 - 15 (ii) a casing formed by the well walls proximate to said impeller,
 - (iii) a liquid inlet and a liquid outlet in said casing, and
 - b) a liquid passageway connecting said wash chamber with said casing inlet, said rotor when rotated in a first direction causing said pump to drain wash liquid from the wash chamber for delivery at
20 said liquid outlet.
3. A dishwasher according to claim 2 wherein said rotor and said drain pump impeller are mounted on a common vertical axis with the drain pump impeller mounted below and coupled to said rotor.
- 25 4. A dishwasher according to claim 2 wherein said drain pump impeller is integrally formed on an end face of said motor rotor.
5. A dishwasher according to claim 3 wherein said drain pump impeller comprises a plurality of symmetrically disposed radial blades protruding from the end face of said motor rotor.
- 30 6. A dishwasher according to claim 1 wherein said electric motor is a salient pole synchronous alternating current motor having a permanent magnet rotor.

7. A dishwasher according to claim 6 wherein said stator includes two pole pairs mounted orthogonally in a flux return ring such that the pole faces lie on a circle coincident with the exterior surface of said well.
- 5 8. A dishwasher according to claim 7 wherein the windings of each pole pair are commutated by a motor drive circuit which provides pulses from the alternating current mains to cause the rotor to start rotating in the desired direction and come up to attain synchronous speed.
- 10 9. A dishwasher according to claim 8 wherein said motor drive circuit includes speed determining means for determining when said rotor has almost reached synchronous speed and a switching means triggered by said speed determining means which disconnects the windings of each pole pair from the drive circuit and connects a single pole pair across the single phase mains supply.
- 15 10. A dishwasher according to claim 9 wherein said switching means connects the windings of the second pole pair in series with a capacitor across the single phase mains supply.
- 20 11. A dishwasher according to claim 8 wherein said drive circuit continues to supply commutation pulses to said pole windings after synchronous speed is attained.
12. A dishwasher comprising:
- a) a wash chamber adapted to accommodate dishes and within which wash liquid is circulated,
 - b) a well provided in the floor of said chamber,
 - 25 c) an electric motor including:
 - (i) a rotor mounted within said well, and
 - (ii) a co-acting stator mounted outside said wash chamber on the exterior surface of said well,
 - d) a wash chamber drain pump including:
 - 30 (i) an impeller located in said well together with said motor rotor, said impeller being driven by said rotor,
 - (ii) a casing formed by the well walls proximate to said impeller,

- (iii) a liquid inlet and a liquid outlet in said casing, and
- e) a liquid passageway connecting said wash chamber with said casing inlet, said rotor when rotated in a first direction causing said pump to drain wash liquid from the wash chamber for delivery at said liquid outlet.

5

13. A dishwasher according to claim 12 further including:

a wash pump impeller driven by said motor rotor, and a spray arm having liquid discharge nozzles rotatably supported in the bottom of said wash chamber for rotation about said wash pump impeller, said spray arm having internal surfaces which define a co-acting casing for said wash pump impeller and which define a volute which allows delivery of wash liquid pumped from said casing to said nozzles.

10

14. A dishwasher according to claim 13 wherein said impeller is configured such that effective pumping only occurs when the motor rotor is rotated in a second direction opposite to said first direction.

15

15. A dishwasher according to claim 13 wherein said spray arm internal surfaces are so configured in relation to said impeller that the reaction force applied thereto by wash liquid accelerated by the impeller and passing into the spray arm volute causes rotation of said spray arm in the direction of rotation of the impeller.

20

16. A dishwasher according to claim 13 wherein said wash pump impeller comprises a hub having a plurality of substantially radially disposed blades extending therefrom to primarily induce radial flow, said impeller rotates about a vertical axis, and the lower edge of each blade is curved out of the radial plane forwardly in the working direction of rotation to induce a small axial flow.

25

17. A dishwasher according to claim 12 further including a second impeller coupled to and mounted above said rotor, said impeller configured such that when the rotor rotates in said first direction a hydrostatic head is generated in said well which equals the pressure generated by the drain pump impeller to thereby prevent leakage of wash liquid pumped by said drain pump upwardly around the rotor.

30

18. A dishwasher according to claim 13 wherein said spray arm central undersurface is open to provide an axial flow inlet for said wash pump, and

further including a first annular aperture provided in the floor of said wash chamber immediately below and in registration with the wash pump inlet,

a second substantially annular aperture provided in the floor of said wash chamber having a diameter much greater than said first aperture, and

5 a plenum below the floor of said wash chamber which allows liquid to flow from the second annular aperture to the first annular aperture for induction up into said wash pump.

19. A dishwasher comprising:

a wash chamber adapted to accommodate dishes and within which wash
10 liquid is circulated,

an electric motor for driving a centrifugal wash pump having a vertical axis drive shaft projecting centrally into the floor of said wash chamber,

a wash pump impeller driven by said motor shaft,

a spray arm having liquid discharge nozzles rotatably supported in the
15 bottom of said wash chamber for rotation about said wash pump impeller, said spray arm having central internal upper and side surfaces which define a co-acting casing for said wash pump impeller and which define a volute which allows delivery of wash liquid pumped from said casing to said nozzles, said spray arm central under surface being open to provide an axial flow inlet for
20 said wash pump,

a first annular aperture provided in the floor of said wash chamber immediately below and in registration with the wash pump inlet,

a second substantially annular aperture provided in the floor of said wash chamber having a diameter much greater than said first aperture, and

25 a plenum below the floor of said wash chamber which allows liquid to flow from the second annular aperture to the first annular aperture for induction up into said wash pump.

20. A dishwasher comprising:

a wash chamber adapted to accommodate dishes and within which wash
30 liquid is circulated,

an electric motor for driving a wash pump,

a wash pump having an inlet and an outlet impeller driven by said motor,

a spray arm generating means which discharges within said wash chamber and which is supplied with wash liquid from the outlet of said wash pump,

5 a substantially annular aperture provided in the floor of said wash chamber having an outer diameter which is significant compared to the dimensions of the wash chamber floor, and

a plenum below the floor of said wash chamber which allows liquid to flow from said annular aperture to the inlet of said wash pump.

21. A dishwasher comprising: a wash chamber adapted to receive dishes
10 to be cleaned, a pump for circulating wash liquid within said chamber, a spray arm having nozzles therein which is rotatably mounted adjacent to the floor of said chamber which receives pressurized wash liquid from said pump and dispenses it through said nozzles into said chamber, and an electrical heating plate which forms part of the wash chamber surface such that at least a
15 portion of the circulating wash liquid comes into thermal contact therewith, said heating plate consisting of a conductive substrate having one or more thick film resistive tracks formed on a surface of said heating plate.

22. A dishwasher according to claim 21 wherein said heating plate forms at least part of the floor of said wash chamber, and the inlet of said pump is
20 located to induct wash liquid from said floor.

23. A dishwasher according to claim 22 wherein said heating plate forms the central portion of said floor, said pump inlet is centrally located, and further including a baffle plate disposed in close proximity above said heating plate and said pump inlet to cause the bulk of the wash liquid inducted by said
25 pump to flow over said heating plate.

24. A dishwasher according to claim 23 wherein said baffle plate extends towards to the periphery of said wash chamber and includes a plurality of peripheral apertures through which wash liquid flows to the chamber floor.

25. A dishwasher comprising:
30 a wash chamber adapted to accommodate dishes and within which wash liquid is circulated, a rack within said chamber which supports dishes above the floor of said chamber, a rotatable spray arm having liquid discharge nozzles located in the bottom of said wash chamber under said rack, a pump

which pressurises said spray arm with wash liquid, and mounting means located centrally in the floor of said chamber which rotatably supports said spray arm, said spray arm in turn comprising a hub portion and two diametrically opposed wing portions extending outwardly therefrom towards the side walls of said chamber, and said wing portions shaped such that they droop downwardly away from the hub portion.

26. A dishwasher according to claim 25 wherein said chamber floor is dished upward in the centre and said wing portions parallel the curvature of the chamber floor.

27. A dishwasher according to claim 25 wherein said spray arm comprises a hollow flat vessel having a vertical thickness substantially less than its horizontal width.

28. A dishwasher according to claim 27 wherein said pump includes an impeller within said chamber and said spray arm is supported in the bottom of said chamber for rotation about said wash pump impeller, and wherein said spray arm has internal surfaces which define a co-acting casing for said wash pump impeller and which define a volute which allows delivery of wash liquid from said casing to said nozzles, said volute surfaces permitting back flow from the extremities of said spray arm into the central portion of said spray arm to supply centrally located nozzles with wash liquid.

29. A dishwasher comprising:

a moulded wash chamber adapted to accommodate dishes and within which wash liquid is circulated,

a moulded reservoir tank integral with said wash chamber and sharing a common side wall with said wash chamber,

said reservoir tank having a horizontal cross-sectional area much less than the horizontal cross-sectional area of said wash chamber,

an electrically controlled water valve in use being connected to a source of water supply which is arranged to discharge into said reservoir tank, and

a syphon means having an inlet in said reservoir tank and an outlet in said wash chamber,

said syphon means being positioned at a height such that when water discharged from said valve into said reservoir tank reaches a level

corresponding to a predetermined volume of wash liquid, syphonic action takes place to drain said predetermined volume of wash liquid from said reservoir tank into said wash chamber.

5 30. A dishwasher according to claim 29 further including a programmed controller and a water level transducer located in said reservoir tank below the water level at which syphonic action occurs, said controller controlling said electrically controlled water valve and receiving as an input the water level transducer signal, and said controller being programmed:

10 (a) to cause filling of said reservoir tank by opening said water valve and maintaining it open until a signal is received from said water level transducer, and

(b) to cause water to be transferred from the reservoir tank to the wash chamber by opening said water valve for a calculated time such that the water level in the reservoir tank will increase to exceed that required for syphonic action to commence.

15

31. A dishwasher according to claim 30 including a second water level transducer located above said first transducer but below the water level at which syphonic action occurs, said controller being programmed to cause water to be transferred from the reservoir tank to the wash chamber by opening said water valve, measuring the time taken for a signal to be received from said second water level transducer, calculating the flow rate from the valve, and calculating from that flow rate the time the water valve should remain open for the water level to rise to a level such that syphonic action occurs.

20

25

32. A dishwasher according to claim 29 further including a programmed controller and a water level transducer located in said reservoir tank below the water level at which syphonic action occurs, a second transducer which detects water flow out of said syphon means, said controller controlling said electrically controlled water valve and receiving as inputs the water level transducer signals, and said controller being programmed:

30

(a) to cause filling of said reservoir tank by opening said water valve and maintaining it open until a signal is received from said water level transducer, and

5 (b) to cause water to be transferred from the reservoir tank to the wash chamber by opening said water valve and maintaining it open until a signal is received from said second transducer.

33. A dishwasher comprising:

a moulded wash chamber adapted to accommodate dishes and within which wash liquid is circulated,

10 a moulded reservoir tank integral with said wash chamber and sharing a common side wall with said wash chamber, said common wall being capable of transmitting heat from the wash chamber to the reservoir tank and vice versa to thereby form a heat exchanger between said wash chamber and said reservoir tank, and means for transferring water from said reservoir tank to
15 said wash chamber.

34. A dishwasher according to claim 33 further including an electrically controlled water valve in use being connected to a source of water supply which is arranged to discharge into said reservoir tank, electrical heating means provided in the floor of said wash chamber, and a programmed
20 controller which controls the operation of said electrically controlled water valve, said electrical heating means and said means for transferring water, said controller programmed such that:

(a) when water is required to be transferred into the wash chamber after the wash chamber has contained wash liquid heated by said heater such water is
25 admitted into said reservoir tank at the termination of wash cycle to be pre-heated by the heat exchange common wall, and

(b) at the start of a drying cycle within the wash chamber, cold water is admitted into said reservoir tank and held within said tank for the duration of the drying cycle to maintain the temperature of the heat exchanger common
30 wall well below the temperature of the wash chamber to thereby condense water vapour produced in the wash chamber during drying onto said wall.

35. A household appliance comprising:

- a) a wash chamber adapted to receive a load to be cleaned and within which wash liquid is circulated,
- b) a well provided in the floor of said chamber,
- c) an electric motor including:
 - (i) a rotor mounted within said well, and
 - (ii) a stator mounted outside said wash chamber circumferentially to the exterior surface of said well,
- d) a wash chamber drain pump including:
 - an impeller located in said well on the rotor shaft,

10 said rotor - drain impeller combination held in working positions without mechanical fastenings or restraints such that they may be disassembled simply by lifting them out of said wash chamber.

36. A dishwasher comprising:

- a) a wash chamber adapted to accommodate dishes and within which wash liquid is circulated,
- b) a well provided in the floor of said chamber,
- c) an electric motor including:
 - (i) a rotor mounted within said well, and
 - (ii) a stator mounted outside said wash chamber circumferentially to the exterior surface of said well,
- d) a wash chamber drain pump including:
 - an impeller located in said well on the rotor shaft,
- e) a wash pump including
 - (i) a wash pump impeller on the rotor shaft, and
 - (ii) a spray arm having liquid discharge nozzles rotatably supported in the bottom of said wash chamber for rotation about said wash pump impeller,

30 said spray arm and rotor - wash impeller - drain impeller combination all held in working positions without mechanical fastenings or restraints such that they may be disassembled simply by lifting them out of said wash chamber.

37. A dishwasher comprising: a wash chamber adapted to receive dishes to be cleaned, a pump for circulating wash liquid within said chamber, a spray arm having nozzles therein which is rotatably mounted adjacent to the floor of

said chamber which receives pressurized wash liquid from said pump and dispenses it through said nozzles into said chamber, said spray arm including at least one nozzle of the spray arm which is directed to produce a transverse jet of wash liquid having components tangential to the circular path traced by said nozzle and downwardly, and a drain sump provided in the floor of said wash chamber having an inlet positioned so as to be directly below and swept by said transverse jet with each rotation of said spray arm.

38. A dishwasher according to claim 37 wherein said pump is provided with a substantially annular inlet in said floor, said inlet is covered by a perforated filter plate, and said jet is directed to sweep over said filter plate.

39. A dishwasher comprising: a wash chamber adapted to receive dishes to be cleaned, a pump for circulating wash liquid within said chamber, a spray arm having nozzles therein which is rotatably mounted adjacent to the floor of said chamber which receives pressurized wash liquid from said pump and dispenses it through said nozzles into said chamber, said spray arm having at least one nozzle directed so as to produce a substantially horizontal and substantially radial jet of wash liquid, and said wash chamber at the height of said horizontal jet having a peripheral deformation in the corners thereof which acts as a vane to deflect said jet vertically such that wash liquid is sprayed vertically in areas of the wash chamber outside the diameter of the spray arm.

40. A dishwasher comprising: a wash chamber adapted to receive dishes to be cleaned, a pump for circulating wash liquid within said chamber, a spray arm having nozzles therein which is rotatably mounted adjacent to the floor of said chamber which receives pressurized wash liquid from said pump and dispenses it through said nozzles into said chamber, said spray arm having at least one nozzle directed so as to produce a substantially horizontal and substantially radial jet of wash liquid, and said wash chamber at the height of said horizontal jet having a peripheral deformation on the planar sections of the walls thereof which acts as a vane to deflect said jet vertically to produce a laminar flow of wash liquid up said wall sections and on to the underside of the roof of said chamber such that wash liquid may drip off said roof to thereby come in contact with the upward facing surfaces of dishes within the chamber.

41. A cabinet for a household appliance of the open sided box type comprising: five side walls rigidly joined along their edges to leave a substantially rectangular opening defined by the free edges of four walls, and a flange around said four free edges, said flange on three edges configured
5 as a portal frame with moment resisting corners and on the fourth edge as a beam linking the ends of the portal frame, the junctions of the beam and portal frame having no substantial resistance to bending moments.

42. A cabinet according to claim 41 wherein said portal frame is configured as two L-shaped portal members having a V-shaped gusset web to support
10 the joint between the two arms of such portal member.

43. A cabinet according to claim 42 wherein said flange is integrally formed from extended portions of the material forming said four side walls, which portions are bent at right angles to said walls and joined at adjacent edges of the flange so formed.

44. A cabinet according to claim 41 wherein the plane of the portal frame is inclined with respect to the plane in which the opposite wall of the cabinet lies.

45. A dishwasher comprising:

(a) a cabinet,
(b) a wash system slidably mounted within said cabinet in such a
20 manner that it may be withdrawn horizontally out of said cabinet for access thereto, said wash system including:

(i) an open top wash chamber adapted to accommodate dishes within which wash liquid is circulated,
(ii) a spray generating means for producing a spray of wash
25 liquid within said chamber,

(iii) means for evacuating wash liquid from said chamber, and
(c) a wash chamber lid mounted in the top of said cabinet, which lid is engaged with the wash chamber opening to sealably close off said wash chamber on retraction of the wash chamber.

46. A dishwasher according to claim 45 further including
30 a reservoir tank mounted as part of said wash chamber,

said reservoir tank having a horizontal cross-sectional area much less than the horizontal cross-sectional area of said wash chamber water delivery means adapted to supply water to said reservoir tank, and

5 a syphon means having an inlet in said reservoir tank and an outlet in said wash chamber,

 said syphon means being positioned at a height such that when water supplied to said reservoir tank reaches a level corresponding to a predetermined volume of wash liquid, syphonic action takes place to drain said predetermined volume of wash liquid from said reservoir tank into said wash
10 chamber.

47. A dishwasher according to claim 45 wherein said evacuating means includes a drain hose and said drain hose is flexible and is configured as a loop when the wash system is fully retracted which can open out to allow said hose to extend with withdrawal of the wash system from said cabinet

15 said loop being provided with a straight length oriented transversely to the direction of movement of said wash system such that when the wash system is fully retracted the loop occupies a space between the wash system and the cabinet which does not exceed the outside diameter of the drain hose.

48. A dishwasher as claimed in claim 45 wherein a water discharge spout is
20 mounted in said cabinet so as to be capable of discharging into said wash chamber when said wash system is fully retracted within said cabinet, a water hose is connected at one end to said discharge spout and adapted at the other end to connect in use to a water supply connection.

49. A dishwasher combination comprising two dishwashers as each claimed
25 in claim 48 wherein said water hoses are each connected to one outlet of dual electrically operated valves, said dual valve having a common connection adapted to connect in use to a household cold water tap.

50. A dishwasher combination comprising two dishwashers as claimed in
claim 48 wherein the outlets of an electrically operated two-way valve provide
30 the cold water supply connections for each dishwasher, and including an electrically operated gate valve adapted to connect in use to a household cold water supply tap and a water hose connecting the outlet of said gate valve to the inlet of said two-way valve.

51. A dishwasher according to claim 45 wherein said lid is mounted in said cabinet by four hinged link members, one end of each member being hingably connected to said cabinet and the other end of each member being hingably connected to said lid to provide the lid with two degrees of freedom such that an inwardly directed force causes said lid to move inwardly and downwardly and an outwardly directed force causes said lid to move outwardly and upwardly, and complementary abutting means provided on said lid and said wash chamber, said means abutting on substantially full retraction of said wash chamber within said cabinet and on initial withdrawal of said wash chamber from within said cabinet with continued displacement of said wash chamber after abutment providing respective closing and opening forces to said lid to cause it to close against or open away from said wash chamber opening.

52. A dishwasher comprising a cabinet, a wash chamber within said cabinet adapted to receive washing liquid to effect washing and to receive dishes to be washed, a horizontally disposed rotatable spray arm mounted in a lower portion of said wash chamber and having spray nozzles, a wash pump having an impeller, said wash pump being arranged to draw wash liquid from a lower part of said wash chamber and deliver said wash liquid to said spray nozzles, an electric motor driving said impeller, and the distance between the lowest level of said motor being of the order of 55mm (fifty five millimetres).

53. An alternating current synchronous motor and starting drive comprising: a stator including at least one pole pair and windings associated therewith, a permanent magnet rotor having at least one pole pair, sensing means for determining the angular position of the rotor, switching means for energising respective stator windings from the alternating current mains, and a controller which monitors the output of said sensing means and the waveform of the alternating current mains and fires the switching means connected to the stator winding with an appropriate segment of mains half-cycle which will cause rotor rotation in the desired direction or will increase the speed of rotor rotation.

54. A motor and drive as claimed in claim 53 including angular speed sensing means which detect the speed of said rotor, said controller switching at least one pair of stator windings continuously to the mains upon said speed

sensing means detecting rotor speed substantially equal to synchronous speed.

55. A motor and drive as claimed in claim 54 including a second switching means and a capacitor in series therewith, and wherein the stator includes two pole pairs, said second switching means adapted to energise the windings of said second pole pair from the alternative current mains through said series capacitor., said controller additionally firing said second switching means on said speed sensing means detecting rotor speed substantially equal to synchronous speed.

56. A motor according to claim 53 wherein said evacuating means includes a drain hose and said drain hose is flexible and is configured as a loop when the wash system is fully retracted which can open out to allow said hose to extend with withdrawal of the wash system from said cabinet

said loop being provided with a straight length oriented transversely to the direction of movement of said wash system such that when the wash system is fully retracted the loop occupies a space between the wash system and the cabinet which does not exceed the outside diameter of the drain hose.

57. A method of manufacturing a stator for a salient pole electric motor comprising the steps of:

- 20 (a) forming a laminated square flux return ring by:
 - (i) providing a continuous strip of workable magnetic material,
 - (ii) cutting notches in one edge of said strip at a pitch equal to the side dimension of said square,
 - (iii) winding said strip edgewise into a square helix by bending the strip edgewise at right angles at each notch, the notches being on the inside of the bend and every fourth notch in registration, until the required stator thickness has been achieved;
- (b) forming salient poles as lengths of magnetic material having end formations complementary to said flux ring notches;
- (c) fitting pre-wound stator coils onto each pole; and
- (d) placing two or four salient poles into each flux return ring such that the salient poles lie in the same plane as said flux ring, extend

diagonally from the corners of the flux ring, and the end formations lock within the complementary notches in the flux ring.

1/25




FIG 1




FIG 2




FIG 3




FIG 4

3/25




FIG 5




FIG 7




FIG 6




FIG 8

4/25





FIG 10






FIG 11

FIG 13




FIG 14





FIG 15



6/25




FIG 12

7/25




FIG 16




FIG 17




FIG 18




FIG 19

8/25




FIG 20




FIG 21

9/25





FIG 23



10/25

FIG 24





FIG 26

11/25




FIG 25




FIG 27




FIG 28




FIG 29





FIG 30

15/25

FIG 31






FIG 32

17/25





FIG 34






FIG 35





FIG 36

19/25



20/25




FIG 38

21/25




FIG 39

22/25




FIG 40

23/25




FIG 41

24/25

FIG 42






FIG 43



25/25

FIG 44



SUBSTITUTE SHEET

INTERNATIONAL SEARCH REPORT

International application No.

PCT/NZ92/00008

A. CLASSIFICATION OF SUBJECT MATTER Int. Cl. ⁵ A47L 15/00, 15/02, 15/08, 15/14, 15/22, H02K 15/02, H02P 1/50 According to International Patent Classification (IPC) or to both national classification and IPC					
B. FIELDS SEARCHED Minimum documentation searched (classification system followed by classification symbols) Int. Cl. ⁵ A47L 15/00, 15/02, 15/08, 15/14, 15/22, H02K 15/02, 21/16, H02P 1/48, 1/50 Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched AU: IPC as above Electronic data base consulted during the international search (name of data base, and where practicable, search terms used) Derwent: IPC as above (H02K with "salient") JAPIO: IPC as above (H02K with "salient")					
C. DOCUMENTS CONSIDERED TO BE RELEVANT					
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to Claim No.			
X	GB,A,1202546 (Candy S.p.A.) 19 August 1970 (19.08.70) All specification	1,12,35,36			
X	US,A,2880740 (Peglow) 7 April 1959 (07.04.59) All specification	1,12,35,36			
X	US,A,3288156 (Jordan) 29 November 1966 (29.11.66) All specification	1,12,35,36			
A	US,A,3457929 (Madden) 29 July 1969 (29.07.69)	1,12,35,36			
<div style="display: flex; justify-content: space-between;"> <div style="text-align: left;"> <input checked="" type="checkbox"/> Further documents are listed in the continuation of Box C. </div> <div style="text-align: left;"> <input checked="" type="checkbox"/> See patent family annex. </div> </div>					
<table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 40%; vertical-align: top;"> <p>* Special categories of cited documents :</p> <p>"A" document defining the general state of the art which is not considered to be of particular relevance</p> <p>"E" earlier document but published on or after the international filing date</p> <p>"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)</p> <p>"O" document referring to an oral disclosure, use, exhibition or other means</p> <p>"P" document published prior to the international filing date but later than the priority date claimed</p> </td> <td style="width: 10%; vertical-align: top; text-align: center;"> <p>"T"</p> <p>"X"</p> <p>"Y"</p> <p>"&"</p> </td> <td style="width: 50%; vertical-align: top;"> <p>later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</p> <p>document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone</p> <p>document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art</p> <p>document member of the same patent family</p> </td> </tr> </table>			<p>* Special categories of cited documents :</p> <p>"A" document defining the general state of the art which is not considered to be of particular relevance</p> <p>"E" earlier document but published on or after the international filing date</p> <p>"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)</p> <p>"O" document referring to an oral disclosure, use, exhibition or other means</p> <p>"P" document published prior to the international filing date but later than the priority date claimed</p>	<p>"T"</p> <p>"X"</p> <p>"Y"</p> <p>"&"</p>	<p>later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</p> <p>document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone</p> <p>document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art</p> <p>document member of the same patent family</p>
<p>* Special categories of cited documents :</p> <p>"A" document defining the general state of the art which is not considered to be of particular relevance</p> <p>"E" earlier document but published on or after the international filing date</p> <p>"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)</p> <p>"O" document referring to an oral disclosure, use, exhibition or other means</p> <p>"P" document published prior to the international filing date but later than the priority date claimed</p>	<p>"T"</p> <p>"X"</p> <p>"Y"</p> <p>"&"</p>	<p>later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</p> <p>document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone</p> <p>document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art</p> <p>document member of the same patent family</p>			
Date of the actual completion of the international search 20 April 1993 (20.04.93)		Date of mailing of the international search report 22 APR 1993 (22.4.93)			
Name and mailing address of the ISA/AU AUSTRALIAN PATENT OFFICE PO BOX 200 WODEN ACT 2606 AUSTRALIA Facsimile No. (06) 2853929		Authorized officer N. Stojadinovic NENAD STOJADINOVIC Telephone No. (06) 2832124			

INTERNATIONAL SEARCH REPORT

International application No.

PCT/NZ92/00008

C(Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate of the relevant passages	Relevant to Claim No.
A	US,A,3406637 (Pearl) 22 November 1968 (22.11.68)	1,12,35,36
A	US,A,3310243 (Duncan) 21 March 1967 (21.03.67)	1,12,35,36
A	US,A,3062226 (Mcmillan) 6 November 1962 (06.11.62)	1,12,19,20,35,36
X	GB,A,1384847 (Industrie A. Zanussi S.p.A.) 26 February 1975 (26.02.75) All specification	19,20
A	GB,A,942273 (Simplex Electric Co. Ltd.) 20 November 1963 (20.11.63)	19,20
A	GB,A,2032769 (Licentia) 19 October 1979 (19.10.79)	21
X	GB,A,1244979 (Hobart Manufacturing. Co.) 2 September 1971 (02.09.71) All specification	19,20,21,29
A	GB,A,2139083 (Bosch-Siemens) 7 November 1984 (07.11.84)	19,20,21,29
A	US,A,1392476 (Boerdeker) 4 October 1921 (04.10.21)	29
A	GB,A,2199734 (Industrie A. Zanussi S.p.A.) 20 July 1988 (20.07.88)	25,37,39,40
A	US,A,1658548 (Darley) 3 July 1924 (03.07.24)	41
A	US,A,1942456 (Rogers) 1 September 1934 (01.09.34)	41
A	US,A,1931996 (Schimpke) 24 October 1933 (24.10.33)	41
X,Y	US,A,4712035 (Forbes) 8 December 1987 (08.12.87)	57
A	See Figs. 1, 2, 5, 24 and specification	53
	See Fig. 29 and specification	
Y	US,A,4816711 (Fritzsche) 28 March 1989 (28.03.89) See Figs. 5, 10 and 11	57
A	FR,A,2358044 (Siemens A.G.) 3 February 1978 (03.02.78)	57

INTERNATIONAL SEARCH REPORT

International application No.

PCT/NZ92/0008

Supplemental Box
(to be used when the space in any of Boxes I to VIII is not sufficient)

Continuation of Box :II

Claim 1 is directed to a dishwasher with a well in the chamber floor, a motor with the rotor within the well and the stator on an external wall of the chamber. These features are common to claims 12, 35 and 36, but do not appear in the remaining independent claims.

Claims 19 and 20 are directed to a dishwasher characterised by an annular aperture in the floor of the chamber and a plenum below said chamber. These features do not appear in the other independent claims.

Claim 21 is directed to a dishwasher characterised by an electric heating plate.

Claim 25 is directed to a dishwasher characterised by a rack and a spray arm with wings which drop downwards from a hub.

Claim 29 is directed to a dishwasher characterised by a moulded chamber with an integral reservoir. C

Claim 33 includes these features and defines the common wall between the chamber and reservoir as acting as a heat exchanger.

Claims 37, 39 and 40 are directed to a dishwasher mainly defining the direction of the jets of washing liquid from the spray arm.

Claim 41 is directed to the structure of a cabinet, characterised by five walls with an open top. No common element of novelty being apparent with the remaining independent claims.

Claim 45 defines a dishwasher wherein the wash system is moved horizontally into and out of the cabinet.

Claim 53 is directed to an A/C synchronous motor, characterised by a stator including at least one pole pair, a permanent magnet rotor having at least one pole pair, switching means and a controller.

Claim 57 is directed to a method of manufacturing of a motor stator, characterised by forming a square flux return ring, forming salient poles, fitting pre wound stator coils and placing two or four salient poles onto each flux return ring.

It is considered that there is no common element of novelty between claims (1, 12, 35, 36) : (19, 20) : (21) : (25) : (29) : (37) : (40) : (41) : (45) : (53) and (57). Therefore there are at least 12 inventions and 9 class marks to be searched.

This Annex lists the known "A" publication level patent family members relating to the patent documents cited in the above-mentioned international search report. The Australian Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

Patent Document Cited in Search Report		Patent Family Member			
GB	1202546	DE	1628555		
GB	1384842	DE	2318780	FR	2180034
		IT	982741	JP	49010130
				IL	41954
				US	3755127
GB	1244979	FR	1599495	US	3465761
US	4712035	AU	65094/86	AU	70817/91
		FR	2595019	FR	2607157
		GB	2183932	GB	2220681
		JP	62114456	NZ	218135
				DE	3638228
				FR	2607158
				IT	1197975
				NZ	232671
US	4816711	CA	1254937	EP	198047
				IT	1200787
FR	2358044	DE	2630806	IT	1084977
				NL	7707649
END OF ANNEX					